

Part No.

FLP1-GV-2M-W1

FieldLab Pressure, 10,000 psi / 700 bar / 70 MPa, 1/4" Male NPT bottom connection, Wireless module installed

A brand new way of thinking about calibration - use this FieldLab to create tests, put them on one or more FieldLabs, log the results and get the data onto a PC easily and quickly.



FLP1-GV-2M-W1

Specs/Attributes

Accuracy - Pressure Measurement	+/- 0.02% of Full Scale (0-20% of Full Scale), +/- 0.1% of Reading (20-100% of Full Scale)
Battery Count	1
Battery Life	1000 Hours
Battery Type	Lithium Ion rechargeable, 4.8 Ah Capacity
Burst Pressure	40000 PSI / 2760 bar / 275 MPa
Calibration Certificate	ISO 17025:2017 Accredited
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Conforms to UL / IEC / EN / AS Standard No. 61010-1, North America - Class 1 Division 1 Groups A-D, T4, (-10 < Ta < 50°C), ATEX - Ex II 1 G Ex ia IIC T4 Ga (-10 < Ta < 50 °C), IECEx - Ex ia IIC T4 Ga (-10 < Ta < 50 °C), UN/DOT 38.3 (Lithium Batteries), Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country Adapters	North America, Europe, United Kingdom, Australia, China
Country of origin	USA
Data Logging	2 million points (onboard)

Specs/Attributes

Engineering Units	atm, bar, cmH2O @4°C, inH2O @39°C, kPa, MPa, mbar, psi, inHg @39°F, kgf / cm^2, mmHg @0°C, Torr, ftH2O @39°F, cmHg @ 0°C, oz / in^2
Harmonized Code	9026.20.0000
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	3.5 in / 90mm Color TFT LCD Display
Materials	Reinforced Polyamide
Max Operating Temperature	120 °F / 50 °C
Max Pressure	10000 PSI / 700 bar / 70 MPa
Max Storage Temperature	165 °F / 75 °C
Measurement Type	Gauge Pressure
Min Operating Temperature	14 °F / -10 °C
Min Storage Temperature	-20 °F / -29 °C
Mounting Holes	3 x M5 Inserts (10 mm deep)
Operating Altitude (max)	10,000 ft (3050 m)
Power Input	90-264 VAC, 50-60 Hz
Primary Power	Battery Power
Process Connection	1/4" Male NPT
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Relative Humidity	0% to 90% (-10 to 35°C) , 0% to 70% (35 to 50°C)
Seal Materials	Teflon, Viton
Sensor Type	High Precision MEMS
USB Connection	USB (Type B)
W1 Radio Installed	Yes
Wetted Materials	316 Stainless Steel
Wireless	Zigbee
Wireless Range	500 ft / 155 m
Weight	2.58 lbs / 1.17 kg
Dimensions	H: 9 in (22.86 cm) x W: 5 in (12.7 cm) x D: 2.5 in (6.35 cm)