

Part No.

# LC20-GY2H-00-B1

*LC20 pressure gauge, 20,000 psi / 140 MPa, 1/4" Female High Pressure bottom conn., Bluetooth radio*

The LC20 is a robust device that measures and displays pressure readings on a large, backlit screen. The LC20 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and live viewing of pressure.



LC20-GY2H-00-B1

## Specs/Attributes

|                           |                                                                                                                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Battery Count             | 2                                                                                                                                                                                                                    |
| Battery Life              | 1000 Hours                                                                                                                                                                                                           |
| Battery Type              | AA Alkaline (IEC-LR6)                                                                                                                                                                                                |
| Bluetooth Radio Installed | Yes                                                                                                                                                                                                                  |
| Calibration Certificate   | ISO 17025:2017 Accredited                                                                                                                                                                                            |
| Certifications            | Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU |
| Contains Wireless Module  | Yes                                                                                                                                                                                                                  |
| Country of origin         | USA                                                                                                                                                                                                                  |
| Data Logging              | PC based (via USB)                                                                                                                                                                                                   |
| Electrical Rating         | 50 mA @ 5 VDC                                                                                                                                                                                                        |
| Harmonized Code           | 9026.20.0000                                                                                                                                                                                                         |
| Ingress Protection        | IP67 (1 meter water submersion for 30 minutes)                                                                                                                                                                       |
| LCD Display               | 2.4 in / 61 mm segmented LCD Display                                                                                                                                                                                 |
| Materials                 | ABS / Polycarbonate Blend, Powder Coated Aluminum                                                                                                                                                                    |

## Specs/Attributes

|                             |                                                                                                         |
|-----------------------------|---------------------------------------------------------------------------------------------------------|
| Max Operating Temperature   | 120 °F / 50 °C                                                                                          |
| Min Operating Temperature   | -4 °F / -20 °C                                                                                          |
| Panel Mount                 | No                                                                                                      |
| Primary Power               | Battery Power                                                                                           |
| Process Connection Location | Bottom mount                                                                                            |
| Protection Class            | Pollution Degree 2 (UL / IEC 61010-1)                                                                   |
| Radio Approvals             | FCC ID 2AA9B04, IC ID 12208A-04, Japan ID 210-107153, Korea - Clause 3, Article 58-2 of Radio Waves Act |
| Radio Type                  | Bluetooth 5 LE                                                                                          |
| Temperature Compensation    | None                                                                                                    |
| USB Connection              | USB (Micro B)                                                                                           |
| Wetted Materials            | 316 Stainless Steel                                                                                     |
| Wireless                    | Bluetooth                                                                                               |
| Wireless Range              | 330 ft / 100 m                                                                                          |
| Connector End 1             | 1/4" Male NPT (ASME B1.20.1)                                                                            |
| Connector End 2             | 9/16-18 (1/4" HF4) Female High Pressure                                                                 |
| Weight                      | 12.6 oz / 355 grams                                                                                     |
| Dimensions                  | H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)                                       |

## Sensor A (Bottom)

|                           |                                                                                                                                                                                                                           |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Burst Pressure            | 80000 PSI / 5515 bar / 550 MPa                                                                                                                                                                                            |
| Max Operating Temperature | 120 °F / 50 °C                                                                                                                                                                                                            |
| Min Operating Temperature | -4 °F / -20 °C                                                                                                                                                                                                            |
| Wrench Size               | 7/8 In<br>23 mm                                                                                                                                                                                                           |
| Measurement Type          | Gauge Pressure                                                                                                                                                                                                            |
| Max Pressure              | 20000 PSI / 1380 bar / 140 MPa                                                                                                                                                                                            |
| Wetted Materials          | 17-4 Stainless Steel                                                                                                                                                                                                      |
| Engineering Units         | atm, bar, cmHg @ 0°C, ftH2O @39°F, inHg @39°F, kgf / cm <sup>2</sup> , MPa, psi                                                                                                                                           |
| Media Compatibility       | Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Light motor oil, Mineral Oil, Natural Gas, Petroleum Based Oil, Ralston Calibration Oil, Skydrol, Transmission fluid, Water, Windshield washer fluid |
| Max Storage Temperature   | 165 °F / 75 °C                                                                                                                                                                                                            |
| Min Storage Temperature   | -40 °F / -40 °C                                                                                                                                                                                                           |
| Sensor Type               | Pressure Sensor                                                                                                                                                                                                           |

**Sensor A (Bottom)**

|                                 |                                                              |
|---------------------------------|--------------------------------------------------------------|
| Materials                       | Stainless Steel                                              |
| Process Connection              | 9/16-18 Female High Pressure (1/4 HP)                        |
| Accuracy - Pressure Measurement | +/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1) |
| Max Vacuum                      | 0.00 InHg / 0.0 kPa                                          |
| Country of origin               | USA                                                          |