

Part No.

LC20-GZ2H-GB2M-00

LC20 pressure gauge, 30000 psi bottom, 5 psi top connection, both 1/4" Male NPT

The LC20 is a robust device that measures and displays pressure readings on a large, backlighted screen. The LC20 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and live viewing of pressure.



LC20-GZ2H-GB2M-00

Specs/Attributes

Battery Count	2
Battery Life	1000 Hours
Battery Type	AA Alkaline (IEC-LR6)
Calibration Certificate	ISO 17025:2017 Accredited
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country of origin	USA
Data Logging	PC based (via USB)
Electrical Rating	50 mA @ 5 VDC
Harmonized Code	9026.20.0000
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display

Specs/Attributes

Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Operating Temperature	120 °F / 50 °C
Max Pressure	3000 PSI / 200 bar / 20 MPa
Min Operating Temperature	-4 °F / -20 °C
Panel Mount	No
Primary Power	Battery Power
Process Connection Location	Bottom mount
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Temperature Compensation	None
USB Connection	USB (Micro B)
W1 Radio Installed	No
Wetted Materials	316 Stainless Steel
Wireless	None
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	9/16-18 (1/4" HF4) Female High Pressure
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)

Sensor A (Bottom)

Country of origin	USA
Max Storage Temperature	165 °F / 75 °C
Min Storage Temperature	-40 °F / -40 °C
Burst Pressure	120000 PSI / 8275 bar / 830 MPa
Max Operating Temperature	120 °F / 50 °C
Min Operating Temperature	-4 °F / -20 °C
Wrench Size	7/8 In 23 mm
Measurement Type	Gauge Pressure
Max Pressure	30000 PSI / 2070 bar / 205 MPa
Wetted Materials	17-4 Stainless Steel
Engineering Units	atm, bar, cmHg @ 0°C, ftH2O @39°F, inHg @39°F, kgf / cm^2, MPa, psi
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Light motor oil, Mineral Oil, Natural Gas, Petroleum Based Oil, Ralston Calibration Oil, Skydrol, Transmission fluid, Water, Windshield washer fluid

Sensor A (Bottom)

Accuracy - Pressure Measurement	+/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1)
Materials	Stainless Steel
Sensor Type	Pressure Sensor
Process Connection	9/16-18 Female High Pressure (1/4 HP)
Max Vacuum	0.00 InHg / 0.0 kPa

Sensor B (Top)

Wrench Size	7/8 In 23 mm
Burst Pressure	20 PSI / 1.4 bar / 140 kPa
Measurement Type	Gauge Pressure
Sensor Type	Pressure Sensor
Engineering Units	atm, bar, cmH2O @4°C, inH2O @39°C, kPa, mbar, psi, inHg @39°F, kgf / cm^2, mmHg @0°C, Torr, Pa, mmH2O @4°C, ftH2O @39°F, cmHg @ 0°C, oz / in^2
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Light motor oil, Mineral Oil, Natural Gas, Petroleum Based Oil, Ralston Calibration Oil, Skydrol, Transmission fluid, Water, Windshield washer fluid, Oxygen (If Oxygen cleaned)
Accuracy - Pressure Measurement	+/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1)
Max Operating Temperature	120 °F / 50 °C
Min Operating Temperature	-4 °F / -20 °C
Process Connection	1/4" Male NPT
Country of origin	USA
Max Pressure	5 PSI / 34 mbar / 30 kPa
Wetted Materials	316 Stainless Steel
Max Vacuum	0.00 InHg / 0.0 kPa