

Part No.

# LC30-GC2M-TX125-B1

LC30 pressure / temperature gauge, +/-15 psi back, 1/4" Male NPT, M12 External Probe connection back, Bluetooth radio

The LC30 is a robust device that measures and displays pressure readings on a large, backlit screen. It is AC powered with a battery backup. The LC30 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and logging pressure.



LC30-GC2M-TX125-B1

## Specs/Attributes

|                           |                                                                                                                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Backup Power              | AAA Alkaline (IEC-LR03)                                                                                                                                                                                              |
| Battery Count             | 2                                                                                                                                                                                                                    |
| Battery Life              | 1000 Hours                                                                                                                                                                                                           |
| Bluetooth Radio Installed | Yes                                                                                                                                                                                                                  |
| Calibration Certificate   | ISO 17025:2017 Accredited                                                                                                                                                                                            |
| Certifications            | Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU |
| Contains Wireless Module  | Yes                                                                                                                                                                                                                  |
| Country of origin         | USA                                                                                                                                                                                                                  |
| Data Logging              | PC based (via USB)                                                                                                                                                                                                   |
| Electrical Rating         | 50 mA @ 5 VDC                                                                                                                                                                                                        |
| Harmonized Code           | 9026.20.0000                                                                                                                                                                                                         |
| Ingress Protection        | IP67 (1 meter water submersion for 30 minutes)                                                                                                                                                                       |
| LCD Display               | 2.4 in / 61 mm segmented LCD Display                                                                                                                                                                                 |
| Materials                 | ABS / Polycarbonate Blend, Powder Coated Aluminum                                                                                                                                                                    |
| Max Operating Temperature | 120 °F / 50 °C                                                                                                                                                                                                       |
| Media Compatibility       | Inert Gas, Natural Gas, Petroleum Based Oil, Water                                                                                                                                                                   |

## Specs/Attributes

|                             |                                                                                                         |
|-----------------------------|---------------------------------------------------------------------------------------------------------|
| Min Operating Temperature   | -4 °F / -20 °C                                                                                          |
| Operating Altitude (max)    | 10,000 ft (3050 m)                                                                                      |
| Panel Mount                 | Yes                                                                                                     |
| Power Input                 | 90-264 VAC, 50-60 Hz                                                                                    |
| Primary Power               | AC Mains Power                                                                                          |
| Process Connection Location | Back mount                                                                                              |
| Protection Class            | Pollution Degree 2 (UL / IEC 61010-1)                                                                   |
| Radio Approvals             | FCC ID 2AA9B04, IC ID 12208A-04, Japan ID 210-107153, Korea - Clause 3, Article 58-2 of Radio Waves Act |
| Radio Type                  | Bluetooth 5 LE                                                                                          |
| Relative Humidity           | 0% to 90% (-10 to 35°C) , 0% to 70% (35 to 50°C)                                                        |
| Temperature Compensation    | None                                                                                                    |
| USB Connection              | USB (Micro B)                                                                                           |
| W1 Radio Installed          | Yes                                                                                                     |
| Wetted Materials            | 316 Stainless Steel                                                                                     |
| Wireless                    | Bluetooth                                                                                               |
| Wireless Range              | 330 ft / 100 m                                                                                          |
| Connector End 1             | 1/4" Male NPT (ASME B1.20.1)                                                                            |
| Weight                      | 12.6 oz / 355 grams                                                                                     |
| Dimensions                  | H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)                                       |

## Sensor A (Back)

|                                 |                                                                                                                                                                                                                                                       |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Resolution                      | 0.001 atm, 0.001 bar, 0.001 cmHg@0°C, 0.001 ftH2O@39°F, 0.001 inHg@32°F, 0.001 kgf/cm^2, 0.001 psi, 0.01 inH2O@39°F, 0.01 KPa, 0.01 mmHg@0°C, 0.01 oz/in^2, 0.01 Torr, 0.1 cmH2O@4°C, 0.1 mbar                                                        |
| Max Vacuum                      | 30 InHg / 101.6 kPa                                                                                                                                                                                                                                   |
| Measurement Type                | Gauge Pressure, Gauge Vacuum                                                                                                                                                                                                                          |
| Accuracy - Pressure Measurement | +/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1)                                                                                                                                                                                          |
| Media Compatibility             | Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Light motor oil, Mineral Oil, Natural Gas, Petroleum Based Oil, Ralston Calibration Oil, Skydrol, Transmission fluid, Water, Windshield washer fluid, Oxygen (If Oxygen cleaned) |
| Engineering Units               | atm, bar, cmH2O @4°C, cmHg @ 0°C, ftH2O @39°F, inHg @39°F, kgf / cm^2, kPa, mbar, mmH2O @4°C, mmHg @0°C, oz / in^2, psi, Torr                                                                                                                         |
| Wrench Size                     | 7/8 In<br>23 mm                                                                                                                                                                                                                                       |
| Sensor Type                     | Pressure Sensor                                                                                                                                                                                                                                       |
| Max Storage Temperature         | 165 °F / 75 °C                                                                                                                                                                                                                                        |

### Sensor A (Back)

|                           |                          |
|---------------------------|--------------------------|
| Min Storage Temperature   | -40 °F / -40 °C          |
| Country of origin         | USA                      |
| Max Pressure              | 15 PSI / 1 bar / 100 kPa |
| Wetted Materials          | 316 Stainless Steel      |
| Max Operating Temperature | 120 °F / 50 °C           |
| Min Operating Temperature | -4 °F / -20 °C           |
| Process Connection        | 1/4" Male NPT            |

### Sensor B (Back)

|                                    |                                                                                     |
|------------------------------------|-------------------------------------------------------------------------------------|
| Max Probe Temperature              | 300 °F / 150 °C                                                                     |
| Min Probe Temperature              | -22 °F / -30 °C                                                                     |
| Thermal Probe                      | 1/4 in / 6.35 mm diameter, 12 in / 30.5 cm long, external cable, 20 ft / 6.1 m long |
| Wetted Materials                   | 316 Stainless Steel                                                                 |
| Measurement Type                   | Temperature                                                                         |
| Media Compatibility                | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water                             |
| Accuracy - Temperature Measurement | +/- (0.15 +0.002* t )°C (IEC 60751 Class A)                                         |
| Country of origin                  | USA                                                                                 |
| Electrical Connection              | M12 female, A Code, Silicone seal, IP67                                             |
| Temperature Units                  | °C, °F, K, R                                                                        |