

Part No.

QTFT-ABS0

M6 x 0.75 MM x male Quick-test, with cap and chain, S.S.

Ideal for situations where frequent calibration of a DP transmitter using the bleeder port is required



QTFT-ABS0

Specs/Attributes

Compatible with	ABB 266DSH, ABB 266DRH, ABB 266MRT, ABB 266MST
Country of origin	USA
Has Cap and Chain	Yes
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	Male Quick-test
Connector End 2	M6 X 0.75 MM Male DP Transmitter/Gauge valve
Weight	1.62 oz / 46 grams
Dimensions	H: 2.7 in (6.86 cm) x W: 0.7 in (1.78 cm) x D: 0.7 in (1.78 cm)