

Part No.

QTFT-NPS0

1/4"-20 UNC Male Bleed Port x male Quick-test adapter, with cap and chain, S.S.

Ideal for situations where frequent calibration of a DP transmitter using the bleeder port is required



QTFT-NPS0

Specs/Attributes

Compatible with	Noshok 600 Series Block and Bleed Valves, Noshok 700 Series Block and Bleed Valves, Noshok 2070 Series Block and Bleed Valves, Noshok 2170 Series Block and Bleed Valves, Parker PGI V-526 Series Block and Bleed Valves, Parker PGI V-527 Series Block and Bleed Valves
Country of origin	USA
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4-20 Male DP Transmitter/Gauge valve
Connector End 2	Male Quick-test
Weight	1.63 oz / 46 grams
Dimensions	H: 2.52 in (6.4 cm) x W: 0.69 in (1.75 cm) x D: 0.69 in (1.75 cm)