

Part No.

QTHA-2MS0-A2473T50-QD

Cylinder adapter, AS2473.2 TYPE 50 - Quick-connect x 1/4" Male NPT adapter, S.S.

Connect to high pressure inert gas cylinders with AS 2473.2 Type 50 valves (Australia).



QTHA-2MS0-A2473T50-QD

Specs/Attributes

Certifications	AS2473.2 Type 50 (Australia)
Country of origin	USA
Dimensions A	0.00 In / 0.00 mm
Dimensions B	0.00 In / 0.00 mm
Materials	Stainless Steel
Max Pressure	5000 PSI / 350 bar / 35 MPa
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water
Seal Materials	Buna-N, Polyurethane
Connector End 1	Type 50 Male AS 2743.2
Connector End 2	1/4" Male NPT (ASME B1.20.1)
Weight	6.98 oz / 200 grams
Dimensions	H: 3.63 in (9.22 cm) x W: 1.25 in (3.18 cm) x D: 1.25 in (3.18 cm)