

Part No.

# QTHA-2MS0-AN-QD

*AN -4 Male 37 degree flare (AN/JIC) x male Quick-test, S.S.*

Connect to any female 37 degree flare adapter or tube



QTHA-2MS0-AN-QD

## Specs/Attributes

|                           |                                                                    |
|---------------------------|--------------------------------------------------------------------|
| Country of origin         | USA                                                                |
| Dimensions A              | 0.00 In / 0.00 mm                                                  |
| Dimensions B              | 0.00 In / 0.00 mm                                                  |
| Has Check Valve           | No                                                                 |
| Materials                 | Stainless Steel                                                    |
| Max Operating Temperature | 140 °F / 60 °C                                                     |
| Max Pressure              | 5000 PSI / 350 bar / 35 MPa                                        |
| Min Operating Temperature | 0 °F / -18 °C                                                      |
| Seal Materials            | Buna-N                                                             |
| Connector End 1           | AN -4 (7/16"-20 thread) Male 37 degree (AN/JIC) Flare              |
| Connector End 2           | Male Quick-test                                                    |
| Weight                    | 1.49 oz / 42 grams                                                 |
| Dimensions                | H: 1.64 in (4.17 cm) x W: 0.75 in (1.91 cm) x D: 0.75 in (1.91 cm) |