

Part No.

# QTHA-3MS0-AN-QD

*AN -6 Male 37 degree flare (AN/JIC) x male Quick-test, S.S.*

Connect to any female 37 degree flare adapter or tube



QTHA-3MS0-AN-QD

## Specs/Attributes

|                           |                                                                   |
|---------------------------|-------------------------------------------------------------------|
| Country of origin         | USA                                                               |
| Dimensions A              | 0.00 In / 0.00 mm                                                 |
| Dimensions B              | 0.00 In / 0.00 mm                                                 |
| Has Check Valve           | No                                                                |
| Materials                 | Stainless Steel                                                   |
| Max Operating Temperature | 140 °F / 60 °C                                                    |
| Max Pressure              | 5000 PSI / 350 bar / 35 MPa                                       |
| Min Operating Temperature | 0 °F / -18 °C                                                     |
| Seal Materials            | Buna-N                                                            |
| Connector End 1           | AN -6 (9/16"-18 thread) Male 37 degree (AN/JIC) Flare             |
| Connector End 2           | Male Quick-test                                                   |
| Weight                    | 1.44 oz / 41 grams                                                |
| Dimensions                | H: 1.5 in (3.81 cm) x W: 0.75 in (1.91 cm) x D: 0.75 in (1.91 cm) |