

Part No.

# QTHA-CMS0-C580-QD

*CGA 580 Quick-connect x Male Quick-test, no check valve, Stainless Steel*

Connect to any CGA 580 cylinder valve without a wrench or thread sealant



QTHA-CMS0-C580-QD

## Specs/Attributes

|                           |                                                                                                                                                                                                                           |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certifications            | CGA 580 (USA)                                                                                                                                                                                                             |
| Country of origin         | USA                                                                                                                                                                                                                       |
| Dimensions A              | 0.00 In / 0.00 mm                                                                                                                                                                                                         |
| Dimensions B              | 0.00 In / 0.00 mm                                                                                                                                                                                                         |
| Materials                 | Stainless Steel                                                                                                                                                                                                           |
| Max Operating Temperature | 225 °F / 105 °C                                                                                                                                                                                                           |
| Max Pressure              | 5000 PSI / 350 bar / 35 MPa                                                                                                                                                                                               |
| Media Compatibility       | Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water |
| Min Operating Temperature | 0 °F / -18 °C                                                                                                                                                                                                             |
| Seal Materials            | Buna-N, Urethane                                                                                                                                                                                                          |
| Connector End 1           | 580 Male CGA 580                                                                                                                                                                                                          |
| Connector End 2           | Male Quick-test                                                                                                                                                                                                           |
| Weight                    | 7.42 oz / 210 grams                                                                                                                                                                                                       |
| Dimensions                | H: 2.7 in (6.86 cm) x W: 1.38 in (3.51 cm) x D: 1.38 in (3.51 cm)                                                                                                                                                         |