

Part No.

QTHA-KIT0

5 pc Quick-test fitting kit - 1/8" MNPT, 1/8" FNPT, 1/4" MNPT, 1/4" FNPT, 1/4" Tube adapters, brass

A kit of the most commonly used adapters so that you have what you need in the field



QTHA-KIT0

Included Items

- 1/8" Male NPT Adapter, Brass - 1/8" male NPT x male Quick-test, no check-valve, brass (QTHA-1MB0)
- 1/8" Female NPT adapter, Brass - 1/8" female NPT x male Quick-test, no check-valve, brass (QTHA-1FB0)
- 1/4" Male NPT Adapter, Brass - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- 1/4" Female NPT adapter, Brass - 1/4" female NPT x male Quick-test, no check-valve, brass (QTHA-2FB0)
- 1/4" Tube adapter, Brass - 1/4" tube fitting x male Quick-test, no check-valve, brass (QTHA-2TB0)

Specs/Attributes

| | |
|--------------------|--|
| Max Pressure | 5000 PSI / 350 bar / 35 MPa |
| Materials | Brass |
| Seal Materials | Buna-N |
| Number of Adapters | 5 |
| Number of Hoses | 0 |
| Country of origin | USA |
| Weight | 7.02 oz / 200 grams |
| Dimensions | H: 7 in (17.78 cm) x W: 5 in (12.7 cm) x D: 1 in (2.54 cm) |

1/8" Male NPT Adapter, Brass QTHA-1MB0

| | |
|-------------------|-------|
| Country of origin | USA |
| Has Check Valve | No |
| Materials | Brass |

1/8" Male NPT Adapter, Brass QTHA-1MB0

| | |
|---------------------------|---|
| Max Operating Temperature | 225 °F / 105 °C |
| Max Pressure | 5000 PSI / 350 bar / 35 MPa |
| Max Vacuum | 0.00 InHg / 0.0 kPa |
| Min Operating Temperature | 0 °F / -18 °C |
| Seal Materials | Buna-N |
| Wrench Size | 9/16 In 15 mm |
| Connector End 1 | 1/8" Male NPT (ASME B1.20.1) |
| Connector End 2 | Male Quick-test |
| Weight | 0.88 oz / 25 grams |
| Dimensions | H: 1.2 in (3.05 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm) |

1/8" Female NPT adapter, Brass QTHA-1FB0

| | |
|---------------------------|--|
| Country of origin | USA |
| Has Check Valve | No |
| Materials | Brass |
| Max Operating Temperature | 225 °F / 105 °C |
| Max Pressure | 5000 PSI / 350 bar / 35 MPa |
| Max Vacuum | 0.00 InHg / 0.0 kPa |
| Seal Materials | Buna-N |
| Wrench Size | 5/8 In 16 mm |
| Connector End 1 | 1/8" Female NPT (ASME B1.20.1) |
| Connector End 2 | Male Quick-test |
| Weight | 1.57 oz / 45 grams |
| Dimensions | H: 1.38 in (3.51 cm) x W: 0.62 in (1.57 cm) x D: 0.62 in (1.57 cm) |

1/4" Male NPT Adapter, Brass QTHA-2MB0

| | |
|---------------------------|--------------------------------|
| Burst Pressure | 20000 PSI / 1380 bar / 140 MPa |
| Country of origin | USA |
| Materials | Brass |
| Max Operating Temperature | 225 °F / 105 °C |
| Max Pressure | 5000 PSI / 350 bar / 35 MPa |
| Max Vacuum | 0.00 InHg / 0.0 kPa |
| Min Operating Temperature | 0 °F / -18 °C |
| Seal Materials | Buna-N |

1/4" Male NPT Adapter, Brass QTHA-2MB0

| | |
|-----------------|--|
| Wrench Size | 9/16 In 15 mm |
| Connector End 1 | 1/4" Male NPT (ASME B1.20.1) |
| Connector End 2 | Male Quick-test |
| Weight | 1.09 oz / 31 grams |
| Dimensions | H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm) |

1/4" Female NPT adapter, Brass QTHA-2FB0

| | |
|---------------------------|--|
| Country of origin | USA |
| Has Check Valve | No |
| Materials | Brass |
| Max Operating Temperature | 225 °F / 105 °C |
| Max Pressure | 5000 PSI / 350 bar / 35 MPa |
| Max Vacuum | 0.00 InHg / 0.0 kPa |
| Seal Materials | Buna-N |
| Wrench Size | 3/4 In 19 mm |
| Connector End 1 | 1/4" Female NPT (ASME B1.20.1) |
| Connector End 2 | Male Quick-test |
| Weight | 2.34 oz / 66 grams |
| Dimensions | H: 1.57 in (3.99 cm) x W: 0.75 in (1.91 cm) x D: 0.75 in (1.91 cm) |

1/4" Tube adapter, Brass QTHA-2TB0

| | |
|---------------------------|--|
| Country of origin | USA |
| Has Check Valve | No |
| Materials | Brass |
| Max Operating Temperature | 225 °F / 105 °C |
| Max Pressure | 5000 PSI / 350 bar / 35 MPa |
| Max Vacuum | 0.00 InHg / 0.0 kPa |
| Seal Materials | Buna-N |
| Connector End 1 | 1/4" Male Tube Fitting |
| Connector End 2 | Male Quick-test |
| Weight | 1.17 oz / 33 grams |
| Dimensions | H: 1.47 in (3.73 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm) |