

Part No.

QTHA-KIT15

Female NPT Gauge Adapter Quick-connect kit

Connect to and calibrate Pressure gauges with Male NPT connections without a wrench or thread sealant



QTHA-KIT15

Included Items

- Process Connection - 1/8" female NPT Quick-connect x female Quick-test, no check-valve, S.S. (QTHA-1FSA-QD)
- Process Connection (Qty 4) - 1/4" female NPT Quick-connect x female Quicktest, no check valve, S.S. (QTHA-2FSA-QD)
- Process Connection - 1/2" female NPT Quick-connect x female Quick-test, no check-valve, S.S. (QTHA-4FSA-QD)

Specs/Attributes

Materials	Stainless Steel
Seal Materials	Buna-N, Teflon
Country of origin	USA
Weight	10.69 oz / 305 grams
Dimensions	H: 7 in (17.78 cm) x W: 5 in (12.7 cm) x D: 1 in (2.54 cm)

Process Connection QTHA-4FSA-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon

Process Connection QTHA-4FSA-QD

Connector End 1	1/2" Female NPT (ASME B1.20.1)
Connector End 2	Female Quick-test
Weight	5.57 oz / 160 grams
Dimensions	H: 1.95 in (4.95 cm) x W: 1.38 in (3.51 cm) x D: 1.38 in (3.51 cm)

Process Connection (Qty 4) QTHA-2FSA-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Connector End 1	1/4" Female NPT (ASME B1.20.1)
Connector End 2	Female Quick-test
Weight	2.99 oz / 85 grams
Dimensions	H: 1.94 in (4.93 cm) x W: 0.95 in (2.41 cm) x D: 0.95 in (2.41 cm)