

Part No.

 **QTHA-KIT28**

QTHA-KIT28

Ralston Quick-test Flare AN/JIC Connection Kit

Connection kit to connect to male or female
AN/JIC 37 degree flare fittings without a
wrench

Included Items

- Male H04 AN/JIC - AN -4 Male 37 degree flare (AN/JIC) x male Quick-test, S.S. (QTHA-2MS0-AN-QD)
- Male H06 AN/JIC - AN -6 Male 37 degree flare (AN/JIC) x male Quick-test, S.S. (QTHA-3MS0-AN-QD)
- Male H08 AN/JIC - 1/2" Male NPT Quick-connect x male Quick-test, S.S. (QTHA-4MS0-QD)
- Female H04 AN/JIC - AN -4 Female 37 degree flare (AN/JIC) x male Quick-test, no check-valve, S.S. (QTHA-2FSF-QD)
- Female H06 AN/JIC - AN -6 Female 37 degree (AN/JIC) flare x male Quick-test adapter, S.S. (QTHA-3FSF-QD)
- Female H08 AN/JIC - AN -8 Female 37 degree flare (AN/JIC) x male Quick-test adapter, S.S. (QTHA-4FSF-QD)
- Female H10 AN/JIC - AN -10 Female 37 degree flare (AN/JIC) x male Quick-test adapter, S.S. (QTHA-5FSF-QD)
- Hose - Quick-test 6900 psi hose, S.S. hose ends, 3 ft (92 cm) long (QSQS-HOS-3ft)
- Bag - Zippered bag to hold hose and adapters, nylon (SM-0084)

Specs/Attributes

Country of origin	USA
Weight	1.78 lbs / 805 grams
Dimensions	H: 6.5 in (16.51 cm) x W: 6.5 in (16.51 cm) x D: 1 in (2.54 cm)

Male H04 AN/JIC QTHA-2MS0-AN-QD

Country of origin	USA
Dimensions A	0.00 In / 0.00 mm
Dimensions B	0.00 In / 0.00 mm
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Connector End 1	AN -4 (7/16"-20 thread) Male 37 degree (AN/JIC) Flare
Connector End 2	Male Quick-test
Weight	1.49 oz / 42 grams
Dimensions	H: 1.64 in (4.17 cm) x W: 0.75 in (1.91 cm) x D: 0.75 in (1.91 cm)

Male H06 AN/JIC QTHA-3MS0-AN-QD

Country of origin	USA
Dimensions A	0.00 In / 0.00 mm
Dimensions B	0.00 In / 0.00 mm
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Connector End 1	AN -6 (9/16"-18 thread) Male 37 degree (AN/JIC) Flare
Connector End 2	Male Quick-test
Weight	1.44 oz / 41 grams
Dimensions	H: 1.5 in (3.81 cm) x W: 0.75 in (1.91 cm) x D: 0.75 in (1.91 cm)

Male H08 AN/JIC QTHA-4MS0-QD

Country of origin	USA
Dimensions A	0.00 In / 0.00 mm
Dimensions B	0.00 In / 0.00 mm
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Connector End 1	1/2" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	7.92 oz / 225 grams
Dimensions	H: 2.23 in (5.66 cm) x W: 1.36 in (3.45 cm) x D: 1.36 in (3.45 cm)

Female H04 AN/JIC QTHA-2FSF-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa

Female H04 AN/JIC QTHA-2FSF-QD

Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Polyurethane, Teflon
Connector End 1	AN -4 (7/16"-20 thread) Female 37 degree (AN/JIC) Flare
Connector End 2	Male Quick-test
Weight	1.73 oz / 49 grams
Dimensions	H: 1.7 in (4.32 cm) x W: 1 in (2.54 cm) x D: 1 in (2.54 cm)

Female H06 AN/JIC QTHA-3FSF-QD

Country of origin	USA
Dimensions A	0.00 In / 0.00 mm
Dimensions B	0.00 In / 0.00 mm
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	170 °F / 77 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Polyurethane, Teflon
Connector End 1	AN -6 (9/16"-18 thread) Female 37 degree (AN/JIC) Flare
Connector End 2	Male Quick-test
Weight	2.72 oz / 77 grams
Dimensions	H: 1.85 in (4.7 cm) x W: 0.94 in (2.39 cm) x D: 0.94 in (2.39 cm)

Female H08 AN/JIC QTHA-4FSF-QD

Country of origin	USA
Dimensions A	0.00 In / 0.00 mm
Has Check Valve	No
Materials	Stainless Steel
Max Pressure	5000 PSI / 350 bar / 35 MPa
Seal Materials	Buna-N, Polyurethane, Teflon
Connector End 1	AN -8 (3/4"-16 thread) Female 37 degree (AN/JIC) Flare
Connector End 2	Male Quick-test
Weight	3.74 oz / 105 grams
Dimensions	H: 2.06 in (5.23 cm) x W: 1.02 in (2.59 cm) x D: 1.02 in (2.59 cm)

Female H10 AN/JIC QTHA-5FSF-QD

Country of origin	USA
-------------------	-----

Female H10 AN/JIC QTHA-5FSF-QD

Dimensions A	0.00 In / 0.00 mm
Dimensions B	0.00 In / 0.00 mm
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	130 °F / 54 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Polyurethane, Teflon
Connector End 1	AN -10 (7/8"-14 thread) Female 37 degree (AN/JIC) Flare
Connector End 2	Male Quick-test
Weight	4.67 oz / 130 grams
Dimensions	H: 2.27 in (5.77 cm) x W: 1.15 in (2.92 cm) x D: 1.15 in (2.92 cm)

Hose QSQS-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	3ft / 0.91 m
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.48 oz / 70 grams

Bag SM-0084

Materials	Zippered Nylon
Country of origin	USA
Weight	3 oz / 85 grams

Bag SM-0084

Dimensions	H: 6.5 in (16.51 cm) x W: 6.5 in (16.51 cm) x D: 0.5 in (1.27 cm)
------------	---