

Part No.

 **QTHA-KIT29**

QTHA-KIT29

Ralston Quick-test Metric Connection Kit

Kit to connect to male and female metric fittings

Included Items

- Female 12x1.5 - 12 x 1.5 mm female quick-connect x male Quick-test, S.S. (QTHA-MFS0-1215-QD)
- Female 20x1.5 - Metric Female x Male Quick-test adapter, Brass (QTHA-MFB0-2015)
- Male 14x1.5 - Male M14 x 1.5mm x Male Quick-test adapter, brass (QTHA-MMB0-1415)
- Male 20x1.5 - Male M20 x 1.5mm x Male Quick-test adapter, brass (QTHA-MMB0-2015)
- Hose - Quick-test 6900 psi hose, brass hose ends, 1 m (3.3 ft) long (QTQT-HOS-1m)
- Bag - Zippered bag to hold hose and adapters, nylon (SM-0084)

Specs/Attributes

Country of origin	USA
Weight	14.45 oz / 410 grams
Dimensions	H: 6.5 in (16.51 cm) x W: 6.5 in (16.51 cm) x D: 1 in (2.54 cm)

Female 12x1.5 QTHA-MFS0-1215-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Connector End 1	1215 Female Metric Parallel Thread
Connector End 2	Male Quick-test
Weight	3.06 oz / 87 grams
Dimensions	H: 1.8 in (4.57 cm) x W: 0.95 in (2.41 cm) x D: 0.95 in (2.41 cm)

Female 20x1.5 QTHA-MFB0-2015

Country of origin	USA
Dimensions A	0.00 In / 0.00 mm
Dimensions B	0.00 In / 0.00 mm
Has Check Valve	No
Materials	Brass

Female 20x1.5 QTHA-MFB0-2015

Max Pressure	5000 PSI / 350 bar / 35 MPa
Seal Materials	Buna-N
Connector End 1	20 x 1.5 Female Metric Parallel Thread
Connector End 2	Male Quick-test
Weight	2.11 oz / 60 grams
Dimensions	H: 1.24 in (3.15 cm) x W: 1.15 in (2.92 cm) x D: 1.15 in (2.92 cm)

Male 14x1.5 QTHA-MMB0-1415

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	5/8 In 16 mm
Connector End 1	14 x 1.5 Male Metric
Connector End 2	Male Quick-test
Weight	1.55 oz / 44 grams
Dimensions	H: 1.63 in (4.14 cm) x W: 0.72 in (1.83 cm) x D: 0.72 in (1.83 cm)

Male 20x1.5 QTHA-MMB0-2015

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	1.063 In 27 mm
Connector End 1	20 x 1.5 Male Metric
Connector End 2	Male Quick-test
Weight	9.73 oz / 275 grams
Dimensions	H: 1.93 in (4.9 cm) x W: 1.21 in (3.07 cm) x D: 1.21 in (3.07 cm)

Hose QTQT-HOS-1m

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	1 m / 3.28 ft
Inner Diameter	0.08 In / 3.00 mm
Length	1.00 m / 3 ft 3 in
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.67 oz / 76 grams

Bag SM-0084

Materials	Zippered Nylon
Country of origin	USA
Weight	3 oz / 85 grams
Dimensions	H: 6.5 in (16.51 cm) x W: 6.5 in (16.51 cm) x D: 0.5 in (1.27 cm)