

Part No.

QTHA-KIT3-SS

Replacement outlet hose and process connection with stainless steel ends

Help reduce downtime by having the correct accessories to do the job



QTHA-KIT3-SS

Included Items

- Quick-test hose, S.S. ends, 3ft long - Quick-test 6900 psi hose, S.S. hose ends, 3 ft (92 cm) long (QSQS-HOS-3ft)
- 1/4" Male NPT adapter, S.S. - 1/4" male NPT x male Quick-test, no check-valve, S.S. (QTHA-2MS0)

Specs/Attributes

Max Pressure	5000 PSI / 350 bar / 35 MPa
Materials	Stainless Steel
Seal Materials	Buna-N
Country of origin	USA
Number of Adapters	1
Number of Hoses	1
Weight	3.42 oz / 97 grams
Dimensions	H: 7 in (17.78 cm) x W: 5 in (12.7 cm) x D: 1 in (2.54 cm)

Quick-test hose, S.S. ends, 3ft long QSQS-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	3ft / 0.91 m
Inner Diameter	0.08 In / 3.00 mm

Quick-test hose, S.S. ends, 3ft long QSQS-HOS-3ft

Length	3 ft / 92 cm
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.48 oz / 70 grams

1/4" Male NPT adapter, S.S. QTHA-2MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	1.01 oz / 29 grams
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)