

Part No.

QTHA-KIT32

Ralston Quick-test Metric Tube Fitting Kit

Connect to multiple sizes of metric tube fittings for testing using a Ralston Quick-test hose



QTHA-KIT32

Included Items

- 6mm Tube - 6 mm tube fitting x male Quick-test, no check-valve, brass (QTHA-MTB0-6mm)
- 8mm Tube - 8mm tube fitting x male Quick-test, no check-valve, brass (QTHA-MTB0-8mm)
- 10mm Tube - 10 mm tube fitting x male Quick-test, no check-valve, brass (QTHA-MTB0-10mm)
- 12 mm Tube - 12mm tube fitting x male Quick-test, no check-valve, brass (QTHA-MTB0-12mm)
- Hose - Quick-test 6900 psi hose, brass hose ends, 1 m (3.3 ft) long (QTQT-HOS-1m)
- Bag - Zippered bag to hold hose and adapters, nylon (SM-0084)

Specs/Attributes

Country of origin	USA
Weight	11.41 oz / 325 grams
Dimensions	H: 6.5 in (16.51 cm) x W: 6.5 in (16.51 cm) x D: 1 in (2.54 cm)

6mm Tube QTHA-MTB0-6mm

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C

6mm Tube QTHA-MTB0-6mm

Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Connector End 1	6 mm Male Tube Fitting
Connector End 2	Male Quick-test
Weight	1.17 oz / 33 grams
Dimensions	H: 1.54 in (3.91 cm) x W: 0.64 in (1.63 cm) x D: 0.64 in (1.63 cm)

8mm Tube QTHA-MTB0-8mm

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Connector End 1	8 mm Male Tube Fitting
Connector End 2	Male Quick-test
Weight	1.57 oz / 45 grams
Dimensions	H: 1.57 in (3.99 cm) x W: 0.67 in (1.7 cm) x D: 0.67 in (1.7 cm)

10mm Tube QTHA-MTB0-10mm

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Connector End 1	10 mm Male Tube Fitting
Connector End 2	Male Quick-test
Weight	1.65 oz / 47 grams
Dimensions	H: 1.55 in (3.94 cm) x W: 0.77 in (1.96 cm) x D: 0.77 in (1.96 cm)

12 mm Tube QTHA-MTB0-12mm

Country of origin	USA
-------------------	-----

12 mm Tube QTHA-MTB0-12mm

Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Connector End 1	12 mm Male Tube Fitting
Connector End 2	Male Quick-test
Weight	2.8 oz / 79 grams
Dimensions	H: 1.72 in (4.37 cm) x W: 1 in (2.54 cm) x D: 1 in (2.54 cm)

Hose QTQT-HOS-1m

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	1 m / 3.28 ft
Inner Diameter	0.08 In / 3.00 mm
Length	1.00 m / 3 ft 3 in
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.67 oz / 76 grams

Bag SM-0084

Materials	Zippered Nylon
Country of origin	USA
Weight	3 oz / 85 grams
Dimensions	H: 6.5 in (16.51 cm) x W: 6.5 in (16.51 cm) x D: 0.5 in (1.27 cm)