

Part No.

QTHR-QT-10m

Quick-test Hose Reel with 10 meter Quick-test hose, brass hose ends

The Quick-test hose reel is an innovative solution for storing Ralston Quick-test hoses. It includes inlet and outlet ports, a brake and locking pin and multiple mounting options.



QTHR-QT-10m

Included Items

- Hose Reel - Quick-test Hose Reel without hose (QTHR-0000)
- Hose - Quick-test 6900 psi hose, brass hose ends, 10 m (32.8 ft) long (QTQT-HOS-10m-NR)

Specs/Attributes

Country of origin	USA
Weight	5.64 lbs / 2.56 kg
Dimensions	H: 393.7 in (1,000 cm) x W: 6.5 in (16.51 cm) x D: 11.5 in (29.21 cm)

Hose Reel QTHR-0000

Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Operating Temperature	140 °F / 60 °C
Country of origin	USA
Materials	Anodized Aluminum, Brass, Powder Coated Steel, Stainless Steel
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water
Min Operating Temperature	-40 °F / -40 °C

Hose Reel QTHR-0000

Weight	5.08 lbs / 2.30 kg
Dimensions	H: 9.5 in (24.13 cm) x W: 6.5 in (16.51 cm) x D: 11.5 in (29.21 cm)

Hose QTQT-HOS-10m-NR

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	10 m / 32.80 ft
Inner Diameter	0.08 in / 3.00 mm
Length	10 m / 32 ft 10 in
Materials	Reinforced Polyamide, Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 inHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 in / 26 mm
Outer Diameter	0.20 in / 6.00 mm
Type	QT
Weight	8.77 oz / 250 grams