

Part No.

# XTHA-FRS0

5/16"-24 UNF DP Transmitter x male Quick-test adapter, S.S.

Connect a Quick-test hose directly to a DP transmitter using the bleeder port when the transmitter is not mounted on a 3 or 5 valve manifold or when the manifold is not easily accessible.



XTHA-FRS0

## Specs/Attributes

|                           |                                                                                                                                                                                                                                            |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Compatible with           | Rosemount 2051 Series DP Pressure Transmitters, Rosemount 3051 Series DP Pressure Transmitters, Yokogawa EJ series DP Pressure Transmitters, Anderson Greenwood M25 Block and Bleed Valves, Anderson Greenwood M251 Block and Bleed Valves |
| Country of origin         | USA                                                                                                                                                                                                                                        |
| Materials                 | Stainless Steel                                                                                                                                                                                                                            |
| Max Operating Temperature | 140 °F / 60 °C                                                                                                                                                                                                                             |
| Max Pressure              | 10000 PSI / 700 bar / 70 MPa                                                                                                                                                                                                               |
| Media Compatibility       | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water                                                                                                                                                                                    |
| Min Operating Temperature | 0 °F / -18 °C                                                                                                                                                                                                                              |
| Seal Materials            | Teflon, Viton                                                                                                                                                                                                                              |
| Wrench Size               | 9/16 In<br>15 mm                                                                                                                                                                                                                           |
| Connector End 1           | 5/16-24 Male DP Transmitter/Gauge valve                                                                                                                                                                                                    |
| Connector End 2           | Male Quick-test XT                                                                                                                                                                                                                         |
| Weight                    | 1.18 oz / 33 grams                                                                                                                                                                                                                         |
| Dimensions                | H: 2.3 in (5.84 cm) x W: 0.65 in (1.65 cm) x D: 0.65 in (1.65 cm)                                                                                                                                                                          |