

Part No.

XTHA-KIT2-1m

10,000 psi Hydraulic Pump with BSPP connections
Conversion kit

Convert 10,000 psi hydraulic pump with BSPP connections to Ralston Quick-test XT



XTHA-KIT2-1m

Included Items

- Reference Connection (Qty 2) - G 1/4" male BSPP (ISO 228/1) x male Quick-test XT, no check-valve, with cap and chain, S.S. (XTFT-2MS0-RS)
- Bonded Seal (Qty 2) - 1/4" male RS bonded seal ring, steel and Buna-N (QTHA-2BR-RS)
- Hose - Quick-test XT 10,000 psi hose, S.S. hose ends, 1 meter long (XTXT-HOS-1m)
- Reference Connection - 1/4" male NPT x male Quick-test XT Adapter, S.S. (XTHA-2MS0)

Specs/Attributes

Country of origin	USA
Weight	3.17 oz / 90 grams
Dimensions	H: 8 in (20.32 cm) x W: 9 in (22.86 cm) x D: 1 in (2.54 cm)

Reference Connection (Qty 2) XTFT-2MS0-RS

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	10000 PSI / 700 bar / 70 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Teflon, Viton
Wrench Size	3/4 In 19 mm
Connector End 1	Male Quick-test XT
Connector End 2	G 1/4 Male BSPP (ISO 228)
Weight	2.51 oz / 71 grams

Reference Connection (Qty 2) XTFT-2MS0-RS

Dimensions	H: 1.83 in (4.65 cm) x W: 0.85 in (2.16 cm) x D: 0.85 in (2.16 cm)
------------	--

Bonded Seal (Qty 2) QTHA-2BR-RS

Max Pressure	0.00 PSI / 0.00 mbar / 0.00 kPa
Max Vacuum	0.00 InHg / 0.0 kPa
Materials	Plated Steel
Seal Materials	Buna-N
Country of origin	USA
Weight	0.08 oz / 2.27 grams
Dimensions	H: 0.81 in (2.06 cm) x W: 0.09 in (0.23 cm) x D: 0.09 in (0.23 cm)

Hose XTXT-HOS-1m

Burst Pressure	40000 PSI / 2760 bar / 275 MPa
Color	Blue
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm
Length	1.00 m / 3 ft 3 in
Materials	Reinforced Polyamide, Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	10000 PSI / 700 bar / 70 MPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	0 °F / -18 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.24 In / 7.00 mm
Type	XT
Weight	3.82 oz / 110 grams

Reference Connection XTHA-2MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	10000 PSI / 700 bar / 70 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Teflon, Viton

Reference Connection XTHA-2MS0

Wrench Size	5/8 In 16 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test XT
Weight	1.23 oz / 35 grams
Dimensions	H: 1.43 in (3.63 cm) x W: 0.7 in (1.78 cm) x D: 0.7 in (1.78 cm)