

Part No.

XTHA-KIT6-6ft

Quick-test XT hose and adapter kit with (2) 6 ft hoses, (2) 1/8" MNPT, (2) 1/4" MNPT adapters

Quick-test XT hose and adapter kit with (2) 6 ft hoses, (2) 1/8" MNPT, (2) 1/4" MNPT adapters



XTHA-KIT6-6ft

Included Items

- Adapter (Qty 2) - 1/8" male NPT x male Quick-test XT Adapter, S.S. (XTHA-1MS0)
- Adapter (Qty 2) - 1/4" male NPT x male Quick-test XT Adapter, S.S. (XTHA-2MS0)
- Hose (Qty 2) - Quick-test XT 10,000 psi hose, S.S. hose ends, 6 feet long (XTXT-HOS-6ft)

Specs/Attributes

Country of origin	USA
Compatible with	Fluke 700HTP-2
Weight	12.37 oz / 350 grams
Dimensions	H: 8 in (20.32 cm) x W: 9 in (22.86 cm) x D: 1 in (2.54 cm)

Adapter (Qty 2) XTHA-2MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	10000 PSI / 700 bar / 70 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Teflon, Viton
Wrench Size	5/8 In 16 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test XT
Weight	1.23 oz / 35 grams
Dimensions	H: 1.43 in (3.63 cm) x W: 0.7 in (1.78 cm) x D: 0.7 in (1.78 cm)

Hose (Qty 2) XTXT-HOS-6ft

Burst Pressure	40000 PSI / 2760 bar / 275 MPa
Color	Blue
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm
Length	6 ft / 2.00 m
Materials	Reinforced Polyamide, Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	10000 PSI / 700 bar / 70 MPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.24 In / 7.00 mm
Type	XT
Weight	3.84 oz / 110 grams